

GENERAL HAND TOOLS



NO. S 30-7 "TOMOSADA" GROUTING GUN FOR CEMENT (JAPAN)

For grouting cement or asphalt into narrow gaps eg. door and window frames, with quick-turn guide for easy cleaning.

Item No.	Nozzle (mm)	Lgth (mm)	Cap. c.c.	Packing (pcs/box)	Price (pc)
030-07-CG10	10 (Straight)	650	1000	6	
030-07-CG18	18 (Straight)	650	1000	6	
030-07-GA	Gasket Assembly for Grouting Gun				



NO. S 30-7X "OPT" GROUTING GUN FOR CEMENT (TAIWAN)


Item No.	Nozzle (mm)	Lgth (mm)	Cap. c.c.	Packing (pcs/box)	Price (pc)
030-07X-CEM1	10 (Straight)	650	900	12	
030-07X-CEM2	15 (Round)	650	900	12	
030-07X-CEM3	18 (Straight)	650	900	12	



NO S 30-8 "KYOWA" HYDRAULIC PRESSURE TEST PUMP (JAPAN)

Item No.	Model No.	Weight (kg)	Dimension L x H x W (mm)	Price (pc)
030-08-T050KP	T-50K-P	3.3	320 x 300 x 200	
030-08-T100K	T-100K	7	370 x 300 x 210	

SPECIFICATIONS	T-50K-P	T-100K
Maximum Pressure	5 Mpa (50kg/cm ²) PSI 700	10 Mpa (100kg/cm ²) PSI 1400
Plunger Diameter	22 mm	22 mm
Stroke	35 mm	35 mm
Rate of Water Suction Per Stroke	13 c.c.	13 c.c.
Capacity of Water Tank	4.5 l Plastic tank	5.2 l Steel tank
Size of Discharge Port	1/4"	1/4"
Accessories (1pc each)	Pressure gauge 1/4 PT, Pressure hose, Union joint 1/2", Bushing 1/2"x1/4"	Pressure gauge 1/4 PT, Ultra high pressure hose 1/4 PF x 1 m, 1/4 Nipple



NO S 30-9 "IIDA" LIVE CENTRE (JAPAN)

"IIDA" Live Centre equipped with triple bearing mechanism. For high speed and medium to heavy radial cutting thrust. Hardened to 61° - 65° RC and Ground.

Item No.	Model No.	Dimensions (mm)						Wt. (g)	Price (pc)
		A	B	C	D	E	L		
030-09-LC2	MT No. 2	24	37	69	40	18	130	440	
030-09-LC4	MT No. 4	32	44	108	45	25	184	1030	
030-09-LC6	MT No. 6	62	82	189	102	55	333	8000	



Only Manual Operation

NO S 30-10 "OPT" DRUM AUGER (TAIWAN) (DRAIN CLEANING TOOL)

Rust-proof drum made of high impact plastic, nor dent or rust. For cleaning of small/medium household drains in showers, sinks or tubes.

Item No.	Model No.	Cable Size	Packing (pcs) per ctn	Price (pc)
030-10-DR0125P	DR0125P	1/4"x25'(6mmx7.6m)	6	