

"LENOX" SAW BLADES - USA

NO. S 85-9W "LENOX" CARBIDE GRIT RECIPROCATING SAW BLADES

High performance in abrasive materials. Cuts through tough materials that resist chip-forming, including ceramics, pipe, man-made stone, brick, marble, and more. Uniformly applied, durable carbide grit particles on a flexible blade provide fast cuts without snagging or binding. For cutting non-metallic materials.



100RG



600RG



800RG

Item No.	Length x Thickness x Width	Application	Price (set of 2pcs)
085-09W-100RG	10" x 1.3mm x 19mm	Cast iron, fiberglass, ceramic wall tile, medium carbide grit clay pipe, stone, brick, plaster, marble.	
085-09W-600RG	6" x 0.8mm x 19mm	Cast iron, fiberglass, ceramic wall tile, medium carbide grit clay pipe, stone, brick, plaster, marble.	
085-09W-800RG	8" x 1.0mm x 19mm	Cast iron, fiberglass, ceramic wall tile, medium carbide grit clay pipe, stone, brick, plaster, marble.	

NO. S 85-9X "LENOX" CARBIDE TIPPED RECIPROCATING SAW BLADES

Carbide tipped reciprocating blades last 10 times longer than standard bi-metal blades in the applications. The triple-chip ground teeth provide 25% faster cutting than standard carbide blades.



6563RCT



6565RCT




8535RCT

Item No.	Length x Thickness, Teeth per inch x Width	Application	Price (pc)
085-09X-6563RCT	6" x 1.3mm x 6T x 19mm	Fiberglass, particle board, pressure-treated woods, plywood, cast aluminum. Contour Back	
085-09X-6565RCT	6" x 1.3mm x 6T x 19mm	Fiberglass, particle board, pressure-treated woods, plywood, cast aluminum. Straight Cutting	
085-09X-8535RCT	8" x 1.3mm x 3T x 19mm	Fiberglass, particle board, pressure-treated woods, plywood, cast aluminum. Straight Back	

NO. S 85-9Y "LENOX" DIAMOND RECIPROCATING SAW BLADES

Nickel alloy-brazed diamond particles maintain sharpness to keep cutting after conventional carbide grit fails. A narrow kerf design enables thinner, faster cut. Unlike bulky snap cutters which crush pipes and leave ragged, uneven cuts, LENOX DIAMOND cuts clean. Durable chrome alloy backing steel provides extra stability.



800RDG

Item No.	Length x Thickness x Width	Application	Price (pc)
085-09Y-800RDG	8" x 1mm x 19mm	Cast iron, tile, brick and architectural stone.	

NO. S 85-9Z "LENOX" AIR RECIPROCATING SAW BLADES

Lenox bi-metal air saw blades are designed with a Matrix II high speed steel cutting edge consisting of 8% cobalt steel, ideal for tough cutting applications. Resistant to heat, wear and breakage.



424T



432T

Item No.	Length x Thickness, Teeth per inch x Width	Application	Price (set of 5 pcs)
085-09Z-424T	4" x 0.6mm x 24T x 12.7mm	For pneumatic machine cutting applications in the automotive repair and sheet metal industries.	
085-09Z-432T	4" x 0.6mm x 32T x 12.7mm	For pneumatic machine cutting applications in the automotive repair and sheet metal industries.	